



#104 ASPHALT CONCRETE PRIMER

TROPICAL ROOFING PRODUCTS' #104 ASPHALT CONCRETE PRIMER is an asphalt based material used as a bonding coat and for priming surfaces prior to the application of cold applied and hot mopped asphalt coatings, roof cements, mastics, and adhesives. #104 Asphalt Concrete Primer is ready to use as it comes from the can.

PREPARATION: Surface must be clean and dry, free of moisture both on and beneath the surface. Scrape off gravel to provide a smooth surface. Sweep roof thoroughly to remove as much dust, dirt, and debris as possible. Use wire brush to remove rust and scale from metal.

APPLICATION: Apply a thin, single coat of #104 over the entire surface with a roller or heavy-duty spray equipment. Brush out any excess immediately after application. Avoid over-application and build-up of surface film. Allow to dry thoroughly before applying adhesives or coatings. Store primer in a warm room overnight before using in cold weather. Drying time varies with weather conditions. **DO NOT HEAT CONTAINER. DO NOT THIN.**

COVERAGE: Proper application will cover approximately 100 square feet per gallon, depending on surface porosity.

PRECAUTIONS: Do not heat container or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT USE** with solvent sensitive insulation, wood shingles or wood flashings. This primer is not recommended over PVC sheet roofing, rubber, shingles of any kind, or old roofs that are too dry and brittle.

CLEANUP: Clean tools with mineral spirits or paint thinner.

CAUTION! COMBUSTIBLE!

Contains petroleum distillate. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION! Avoid contact with skin and breathing of vapor. CLOSE AIR INTAKES on roof until solvents dissipate. KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Contains volatile solvents that might contaminate potable water.

MAXIMUM V.O.C = 350 G/L
CONSISTENCY — Black Liquid
WEIGHT — 7.7+/- .2 lbs. per gal
FLASH POINT (T.C.C.) — 105°F+
DRYING TIME — Average: 3 hrs. to touch

ASTM D-41
FED SPEC SS-A-701

www.tropicalroofingproducts.com



FLORIDA
1904 SW 31st Ave.
Hallandale, FL 33009
fax: 954.963.2033
toll-free: 800.432.2855

CALIFORNIA
14435 Macaw Street
La Mirada, CA 90638
fax: 714.670.1605
toll-free: 877.827.2622

TEXAS
1225 Brai Drive, P.O. Box 5335
Port Arthur, TX 77640
fax: 409.727.4647
toll-free: 866.727.0091

