



# #911 ETERNALASTIC WHITE ELASTOMERIC ROOF COATING

**TROPICAL ROOFING PRODUCTS' # 911 ETERNALASTIC White Elastomeric Roof Coating** is a high quality, Energy Star approved, Title 24 compliant, Dade County Approved, 100% acrylic-based elastomeric, designed specifically for the rigors of professional roofing. This tough, durable coating will dramatically reduce roof temperatures while protecting and repairing the underlying roof. The 100% acrylic base provides superior adhesion on a wide variety of substrates, while simultaneously having extremely high elastomeric properties. High-grade biocides are added to eliminate mold and mildew thoroughly and completely, while not affecting cure time. A high pigment count gives the needed hiding power our industry demands.

**PREPARATION:** Surface must be clean and dry, free of moisture both on and beneath the surface. Pressure wash roof thoroughly to remove as much dust, dirt, and debris as possible. After careful inspection of entire roof, repair all holes, cracks, tears or breaks with reinforcing fabric and #950 Eternamastic. #950 Eternamastic repairs can usually be coated within 24 hours. Coat newly applied asphalt emulsion as soon as the emulsion can take foot traffic without scuffing the surface, normally 7-10 days.

**APPLICATION:** Apply on warm, sunny days, preferably in the morning hours to provide maximum cure time. #911 Eternalastic can be applied to a dry or slightly damp, but not wet, surface. Water must be swept out of all puddles prior to application of #911. Stir #911 thoroughly before application to achieve a uniform consistency. Apply with a heavy-duty paint roller or heavy-duty spray equipment. When applied with roller or brush, strokes should be kept in one direction. Apply second coat perpendicular to the first. Allow at least four hours between coats and 24-48 hours for full cure, dependent upon weather conditions. Relative humidity will directly affect drying/curing time. Avoid over-application. **DO NOT HEAT CONTAINER. DO NOT THIN.**

**COVERAGE:** Proper application will cover approximately 100 square feet per 1-1.5 gallons of coating, dependent upon roof porosity. **Two coats are required.**

**PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F or above 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS.** Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT ALLOW PRODUCT TO FREEZE.** Do not heat container or store at temperatures greater than 120°F. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. **DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.**

**CLEANUP:** If coating has dried, clean tools with mineral spirits or paint thinner. If coating is still wet, clean up with warm soapy water.

## CAUTION!

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

**MAXIMUM V.O.C = 49 G/L**  
SOLAR REFLECTIVE, D.O.E. — .86  
EMISSIVITY, D.O.E. — .89  
WEIGHT — 11.3 lbs. per gal  
VOLUME SOLIDS — 62%  
WEIGHT SOLIDS — 79%  
INITIAL ELONGATION — 160%  
PERMEANCE — 3.9

**ASTM D-6083**

**CALIFORNIA  
Title 24 Compliant**

[www.tropicalroofingproducts.com](http://www.tropicalroofingproducts.com)



FLORIDA  
1904 SW 31st Ave.  
Hallandale, FL 33009  
fax: 954.963.2033  
toll-free: 800.432.2855

CALIFORNIA  
14435 Macaw Street  
La Mirada, CA 90638  
fax: 714.670.1605  
toll-free: 877.827.2622

TEXAS  
1225 Brai Drive, P.O. Box 5335  
Port Arthur, TX 77640  
fax: 409.727.4647  
toll-free: 866.727.0091

