



# #972 SEBS ELASTOMERIC ROOF COATING

**TROPICAL ROOFING PRODUCTS' #972 SEBS Elastomeric Roof Coating** is a single component block copolymer elastomeric fluid applied coating. The coating needs no intermixing, is easy to apply, and has excellent surface appearance. #972 SEBS Elastomeric Coating provides excellent elongation properties, cold weather pliability, chemical, weather, and water resistance.

**USES:** #972 SEBS Elastomeric Coating may be applied to metal, steel, concrete, aluminum, brick, polyurethane, wood, and fiberglass surfaces. The coating also can be used to re-coat existing acrylic or polyurethane coatings and most painted surfaces. #972 SEBS Elastomeric Coating may be applied to APP, SBS, and BUR roofing.

**PREPARATION:** All surfaces to be coated must be clean, dry, and free from dirt, oil, grease, and rust. Newly poured concrete must cure a minimum of 30 days prior to application of #972. Metal and wood must be primed with Elastomeric Primer at the rate of 1/2 to 3/4 gallon per 100 square feet.

**APPLICATION:** Recommended application for #972 SEBS Elastomeric Coating is by brush, spray, or roller. Apply two gallons per 100 square feet in two applications (one gallon of base and one gallon of top coating). Allow base coat (Stain Blocker) to cure thoroughly prior to application of the finish coat. Apply at temperature 45°F and rising. Curing will take 12 to 24 hours dependent upon ambient temperatures and humidity.

**CARE OF EQUIPMENT:** Equipment and tools may be cleaned with petroleum solvents, mineral spirits, or paint thinner. Take necessary precautions when handling combustible material.

**PRECAUTIONS:** Keep away from heat, sparks, and open flame. In interior areas, provide for proper ventilation or respiratory equipment. Use proper safety equipment.

**WARNING:** Avoid breathing fumes and prolonged contact with skin. Do not take internally. **DANGER!** Harmful or fatal if swallowed. Do not induce vomiting. Call a physician immediately. Keep container covered when not in use. Do not thin. **DO NOT HEAT CONTAINER** or store at temperatures greater than 120°F. Be sure lid is tight and pail is secure when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

## CAUTION!

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

**MAXIMUM V.O.C = 550 G/L**  
ELONGATION — 875%  
PERMEANCE — 1.3  
VISCOSITY @ 77° F, KU— 115 +/- 5  
DENSITY(WPG) — 9.5 +/- .2

[www.tropicalroofingproducts.com](http://www.tropicalroofingproducts.com)



FLORIDA  
1904 SW 31st Ave.  
Hallandale, FL 33009  
fax: 954.963.2033  
toll-free: 800.432.2855

CALIFORNIA  
14435 Macaw Street  
La Mirada, CA 90638  
fax: 714.670.1605  
toll-free: 877.827.2622

TEXAS  
1225 Brai Drive, P.O. Box 5335  
Port Arthur, TX 77640  
fax: 409.727.4647  
toll-free: 866.727.0091