



#104 ASPHALT CONCRETE PRIMER

TROPICAL ROOFING PRODUCTS' #104 ASPHALT CONCRETE PRIMER is a solvent-based bond coat and penetrating sealer for priming most surfaces prior to application of cold applied or hot mopped asphalt coatings, roof cements, adhesives, asphalt damp proofing and waterproofing. Not recommended as a stand-alone roof coating. Meets ASTM D 41, FED SPEC SS-A-701, Miami-Dade NOA.

PREPARATION: Surface must be clean and dry, free of moisture both on and beneath the surface. Scrape off gravel to provide a smooth surface. Sweep roof thoroughly to remove as much dust, dirt, and debris as possible. Use wire brush to remove rust and scale from metal.

APPLICATION: Apply a thin, single coat of #104 over the entire surface with a roller or heavy-duty spray equipment. Brush out any excess immediately after application. Avoid over-application and build-up of surface film. Allow to dry thoroughly before applying adhesives or coatings. Store primer in a warm room overnight before using in cold weather. Drying time varies with weather conditions.

COVERAGE: Proper application will cover approximately 100 square feet per gallon, depending on surface porosity.

PRECAUTIONS: DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT USE** with solvent sensitive insulation, wood shingles or wood flashings. This primer is not recommended over PVC sheet roofing, rubber, shingles of any kind, or old roofs that are too dry and brittle.

CLEANUP: Clean tools with mineral spirits or paint thinner.

Contains petroleum distillate. Keep away from heat and flame. **USE ONLY WITH ADEQUATE VENTILATION!** Avoid contact with skin and breathing of vapor. **CLOSE AIR INTAKES** on roof until solvents dissipate. **KEEP OUT OF REACH OF CHILDREN.** Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Contains volatile solvents that might contaminate potable water

MAXIMUM V.O.C = 350 G/L
CONSISTENCY — BLACK LIQUID
WEIGHT — 7.7+/- .2 LBS. PER GAL
FLASH POINT (T.C.C.) — 105°F+
SERVICE TEMPERATURE (RANGE) — 40°F–90°F
DRYING TIME — AVERAGE: 3 HRS. TO TOUCH

ASTM D 41
FED SPEC SS-A-701



FLORIDA
1904 SW 31ST AVE
HALLANDALE, FL 33009
800.432.2855

CALIFORNIA
14435 MACAW STREET
LA MIRADA, CA 90638
877.827.2622

TEXAS
1225 BRAI DRIVE
PORT ARTHUR, TX 77640
866.727.0091