



## #363 FIBERED EMULSION

**TROPICAL ROOFING PRODUCTS' #363 FIBERED EMULSION** is a fiber reinforced water based roof and waterproof coating that is solvent free. Ideal for use as a surface coating for built-up roofing, metal, masonry surfaces, and for pipes and tanks above or below ground level. Will not run, sag, crack, or "alligator" under most weather conditions. Meets and exceeds all the requirements of ASTM D 1227, Type II, Class I.

**PREPARATION:** All surfaces must be clean, have proper drainage, and be free from rust, dirt, and all other foreign matter. Clean all cracks, holes, and damaged areas, repairing when necessary and allow repairs to thoroughly cure.

**APPLICATION:** Apply #363 by roofing brush, roller, or spray, evenly covering the surface. Two coats are recommended. Allow to dry completely between coats. Dry time is usually 6-24 hours in dry or hot weather conditions. In cool or damp weather drying will be slower, 2-7 days.

**COVERAGE:** Apply at the rate of approximately 3-4 gallons per 100 square feet per coat as a topical protective coating and 6-8 gallons total for restoration systems.

**PRECAUTIONS: DO NOT ALLOW TO FREEZE. DON'T THIN. DO NOT HEAT CONTAINER** or store at temperatures greater than 120°F. Do not apply when ambient temperature is below 55°F or if temperatures fall below 40°F within 48 hours. Application over hot applied asphalt may not prevent alligating. This coating is not recommended over rubber, PVC sheet roofing or old roofs that are too dry and brittle. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

**CAUTION: DO NOT TAKE INTERNALLY! KEEP OUT OF REACH OF CHILDREN.**

Use protective measures to avoid contact with eyes and skin. If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! CAUTION! KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

**Calif. Prop.65 Chemical Warning (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ)** Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm may be found in various Tropical Roofing Products' petroleum based products and their vapors. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

**DO NOT USE IF RAIN IS IMMINENT - COATING MUST BE DRY BEFORE EXPOSURE TO WATER**

MAXIMUM V.O.C = 30 G/L  
WATER SOLUABLE  
BOILING POINT — 212°F  
FLASH POINT — NONE  
VAPOR DENSITY — HEAVIER THAN AIR

ASTM D 1227, TYPE II, CLASS I



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091