



#365 MODIFIED EMULSION

TROPICAL ROOFING PRODUCTS' #365 MODIFIED EMULSION is a versatile water based elastomeric roof and waterproof coating ideal for use as a protective coating for built-up roofing, metal, masonry surfaces, pipes and tanks above or below ground level, SBS modified and APP modified (torch down). Cold applied, corrosion-resistant and waterproof when dry. Meets and exceeds all the requirements of ASTM D 1227, Type III, Class I.

PREPARATION: All surfaces must be clean, have proper drainage, and be free from rust, dirt and all other foreign matter. Clean all cracks, holes, and damaged areas, repairing when necessary and allow repairs to thoroughly cure.

APPLICATION: Apply #365 by roofing brush, roller or spray, evenly covering the surface. Two coats are recommended. Allow to dry completely between coats. Dry time is usually 6-24 hours in dry or hot weather conditions. In cool or damp weather drying will be slower, 2-7 days.

COVERAGE: Apply at the rate of approximately 2 – 3 gallons per 100 square feet, dependent upon roof surface.

PRECAUTIONS: DO NOT ALLOW TO FREEZE. DON'T THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Do not apply when ambient temperature is below 55°F or if temperatures below 40°F within 48 hours. Application over hot applied asphalt may not prevent alligating. This coating is not recommended over rubber, PVC sheet roofing or old roofs that are too dry and brittle. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

CAUTION: DO NOT TAKE INTERNALLY! KEEP OUT OF REACH OF CHILDREN.

Use protective measures to avoid contact with eyes and skin. If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! CAUTION! KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

Calif. Prop.65 Chemical Warning (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ) Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm may be found in various Tropical Roofing Products' petroleum based products and their vapors. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

DO NOT USE IF RAIN IS IMMINENT - COATING MUST BE DRY BEFORE EXPOSURE TO WATER

MAXIMUM V.O.C = 30 G/L
WATER SOLUABLE
BOILING POINT — 212°F
FLASH POINT — NONE
VAPOR DENSITY — HEAVIER THAN AIR

ASTM D 1227, TYPE III, CLASS I



FLORIDA
1904 SW 31ST AVE
HALLANDALE, FL 33009
800.432.2855

CALIFORNIA
14435 MACAW STREET
LA MIRADA, CA 90638
877.827.2622

TEXAS
1225 BRAI DRIVE
PORT ARTHUR, TX 77640
866.727.0091