



Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/18/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Tropical - #901 White Elastomeric Roof Coating
Product code : TRO-901
Formula : 700-TRO-901

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Elastomeric Roof Coating

1.3. Details of the supplier of the safety data sheet

TROPICAL ROOFING PRODUCTS
1904 S.W. 31ST Ave.
HALLANDALE, FL 33009 - UNITED STATES
T 954-983-3434
technical@tropicalroofingproducts.com - www.tropicalroofingproducts.com

1.4. Emergency telephone number

Emergency number : 800-424-9300
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Carc. 2 H351

Full text of H-statements: see section 16

2.2. Label elements

GHS-US labelling

0

Hazard pictograms (GHS-US) :



GHS08

GHS09

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H351 - Suspected of causing cancer
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear protective gloves, eye protection
P308+P313 - If exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
latex,liquid,synthetic		20 - 40	Not classified
calcium carbonate	(CAS No) 471-34-1	30 - 40	Not classified
titanium(IV) oxide	(CAS No) 13463-67-7	0 - 10	Carc. 2, H351
zinc oxide	(CAS No) 1314-13-2	0.1 - 2	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2-propanediol	(CAS No) 57-55-6	0.6 - 1.2	Not classified
benzophenone	(CAS No) 119-61-9	0 - 1	Carc. 2, H351
5-chloro-2-methyl-4-isothiazolin-3-one	(CAS No) 26172-55-4	0 - 0.5	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Assure fresh air breathing.
- First-aid measures after skin contact : Wash with water and soap. Rinse with water. Wash skin with plenty of water.
- First-aid measures after eye contact : Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating. Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Drink plenty of water. Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/injuries after skin contact : May cause moderate irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue.
- Symptoms/injuries after ingestion : No data available.
- Chronic symptoms : No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Non combustible. Not flammable.
- Reactivity : No data available.

5.3. Advice for firefighters

- Firefighting instructions : No specific fire-fighting instructions required.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Use personal protective equipment as required. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.
- Hygiene measures : Wash Always wash hands after handling the product thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong bases. Strong acids.
- Storage temperature : 4 - 38 °C
- Storage area : Keep only in the original container. Protect against frost.
- Special rules on packaging : Keep only in original container. meet the legal requirements.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tropical - #901 White Elastomeric Roof Coating		
ACGIH	Not applicable	
OSHA	Not applicable	
titanium(IV) oxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (Titanium dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
OSHA	Not applicable	
latex,liquid,synthetic		
ACGIH	Not applicable	
OSHA	Not applicable	
1,2-propanediol (57-55-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
5-chloro-2-methyl-4-isothiazolin-3-one (26172-55-4)		
ACGIH	Not applicable	
OSHA	Not applicable	
benzophenone (119-61-9)		
ACGIH	Not applicable	
OSHA	Not applicable	
calcium carbonate (471-34-1)		
ACGIH	Not applicable	

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

calcium carbonate (471-34-1)		
OSHA	Not applicable	

zinc oxide (1314-13-2)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (Zinc oxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (Zinc oxide; USA; Short time value; TLV - Adopted Value; Respirable fraction)
ACGIH	Remark (ACGIH)	Metal fume fever
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Face shield. Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless
Odour	: characteristic
Odour threshold	: No data available
pH	: > 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: < 0 °C
Boiling point	: > 100 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 12.3 lb/gal
Solubility	: Water: ≈ 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)

1,2-propanediol (57-55-6)	
LD50 oral rat	22000 mg/kg (Rat, Experimental value)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (24 h, Rabbit, Experimental value)
ATE US (oral)	22000.000 mg/kg bodyweight

benzophenone (119-61-9)	
LD50 dermal rabbit	35535 mg/kg bodyweight (Rabbit, Experimental value, Dermal)
ATE US (oral)	2895.000 mg/kg bodyweight
ATE US (dermal)	35535.000 mg/kg bodyweight

calcium carbonate (471-34-1)	
LD50 oral rat	6450 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Literature study; >2000 mg/kg; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 3 mg/l/4h (Rat; Experimental value)
ATE US (oral)	6450.000 mg/kg bodyweight

zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	> 5.7 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation : Not classified
pH: > 8.5

Serious eye damage/irritation : Not classified
pH: > 8.5

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

benzophenone (119-61-9)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : May cause moderate irritation.

Symptoms/injuries after eye contact : Irritation of the eye tissue.

Symptoms/injuries after ingestion : No data available.

Chronic symptoms : No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Ecology - water : Very toxic to aquatic life with long lasting effects.

titanium(IV) oxide (13463-67-7)	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

1,2-propanediol (57-55-6)	
LC50 fish 1	51600 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Experimental value)
LC50 fish 2	40613 mg/l (Other, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
ErC50 (algae)	24200 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

benzophenone (119-61-9)	
LC50 fish 1	15.3 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	6.784 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
ErC50 (algae)	3.5 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

calcium carbonate (471-34-1)	
EC50 Daphnia 1	> 100 % (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	> 14 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)

zinc oxide (1314-13-2)	
EC50 Daphnia 2	0.33 - 0.66 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Read-across)
Threshold limit algae 1	0.136 mg/l (IC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

Tropical - #901 White Elastomeric Roof Coating	
Persistence and degradability	Not established.

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable. Low potential for mobility in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

latex,liquid,synthetic	
Persistence and degradability	Biodegradability in soil: no data available.
Biochemical oxygen demand (BOD)	0.01 g O ₂ /g substance

1,2-propanediol (57-55-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.96 - 1.08 g O ₂ /g substance
Chemical oxygen demand (COD)	1.63 g O ₂ /g substance
ThOD	1.69 g O ₂ /g substance

5-chloro-2-methyl-4-isothiazolin-3-one (26172-55-4)	
Persistence and degradability	Contains non readily biodegradable component(s).

benzophenone (119-61-9)	
Persistence and degradability	Readily biodegradable in water.

calcium carbonate (471-34-1)	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil.
ThOD	Not applicable (inorganic)

zinc oxide (1314-13-2)	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Low potential for adsorption in soil.
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

Tropical - #901 White Elastomeric Roof Coating	
Bioaccumulative potential	Not established.

titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

latex,liquid,synthetic	
Bioaccumulative potential	Not bioaccumulative.

1,2-propanediol (57-55-6)	
BCF other aquatic organisms 1	0.09
Log Pow	-1.07 (Experimental value, EU Method A.8: Partition Coefficient, 20.5 °C)
Bioaccumulative potential	Not bioaccumulative.

5-chloro-2-methyl-4-isothiazolin-3-one (26172-55-4)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

benzophenone (119-61-9)	
BCF fish 1	3.4 - 12 (8 week(s), Oryzias latipes, Literature)
Log Pow	3.18 (Weight of evidence approach, Other, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

calcium carbonate (471-34-1)	
Log Pow	-2.12 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.

zinc oxide (1314-13-2)	
Log Pow	1.53 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2-propanediol (57-55-6)	
Surface tension	71.6 mN/m (21.5 °C, 1.01 g/l)
Log Koc	0.46 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

5-chloro-2-methyl-4-isothiazolin-3-one (26172-55-4)	
Ecology - soil	No (test)data on mobility of the components available.

benzophenone (119-61-9)	
Surface tension	45.1 mN/m (20 °C)
Ecology - soil	Low potential for mobility in soil.

zinc oxide (1314-13-2)	
Log Koc	log Koc,2.2; Literature study

12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Avoid release to the environment, Do not discharge into drains or the environment, Do not discharge into the sewer.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT	
Transport document description	: Not Regulated (Water Based Material - KEEP FROM FREEZING)
UN-No.(DOT)	: Not Regulated (Water Based Material - KEEP FROM FREEZING)

Additional information

Other information	: No supplementary information available.
-------------------	-------------------------------------------

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Tropical - #901 White Elastomeric Roof Coating

Subject to reporting requirements of United States SARA Section 313

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

	CAS No	
latex,liquid,synthetic		20 - 40%
5-chloro-2-methyl-4-isothiazolin-3-one	CAS No 26172-55-4	0 - 0.5%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

benzophenone (119-61-9)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
--------------------------	----------------------------------------------------------------------------------------

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

benzophenone (119-61-9)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Tropical - #901 White Elastomeric Roof Coating()

U.S. - California - Proposition 65 - Carcinogens List

Yes

U.S. - California - Proposition 65 - Developmental Toxicity

No

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

No

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

No

State or local regulations

U.S. - New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

benzophenone (119-61-9)

U.S. - California - Proposition 65 - Carcinogens List

U.S. - California - Proposition 65 - Developmental Toxicity

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

No significant risk level (NSRL)

Yes

No

No

No

titanium(IV) oxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

1,2-propanediol (57-55-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

zinc oxide (1314-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.

Tropical - #901 White Elastomeric Roof Coating

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 0 Minimal Hazard
Physical : 0 Minimal Hazard

ZLF-PMS 364 CUSTOM TEMPLATE

All information contained in this MSDS is based on current technical data believed to be accurate and reliable. Additions of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since these conditions are outside our control, we furnish this MSDS without any express or implied warranties.