



#960 ETERNALASTIC ACRYLIC METAL PRIMER

TROPICAL ROOFING PRODUCTS' # 960 ETERNALASTIC METAL PRIMER is a professional grade, environmentally-friendly water-based primer designed for use on rusted metal surfaces. To be used when applying Eternalastic product to any structural metal surface. Promotes coating adhesion and is easily applied with roller or airless sprayer .

COVERAGE: Apply at a rate of approximately 0.5 gallon per 100 square feet.

PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48–72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry.
DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

CLEANUP: Clean tools with mineral spirits or paint thinner

CAUTION! COMBUSTIBLE!

KEEP OUT OF REACH OF CHILDREN. Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!**

MAXIMUM V.O.C = 207 G/L
VISCOSITY — 80-90 KU
WEIGHT SOLIDS — 47%
WET APPEARANCE — WHITE
DRY APPEARANCE — WHITE
DRYING TIME — AVERAGE: 2 HOURS



FLORIDA
1904 SW 31ST AVE
HALLANDALE, FL 33009
800.432.2855

CALIFORNIA
14435 MACAW STREET
LA MIRADA, CA 90638
877.827.2622

TEXAS
1225 BRAI DRIVE
PORT ARTHUR, TX 77640
866.727.0091