



## #972 SEBS ELASTOMERIC ROOF COATING

**TROPICAL ROOFING PRODUCTS' #972 SEBS ELASTOMERIC ROOF COATING** is a single component block copolymer elastomeric fluid applied waterproof coating. The coating is easy to apply, and has excellent surface appearance. #972 SEBS Elastomeric Coating provides excellent elongation properties, cold weather pliability, chemical, weather, and water resistance. #972 SEBS Elastomeric Coating may be applied to metal, steel, concrete, aluminum, brick, polyurethane, wood, and fiberglass surfaces. The coating also can be used to re-coat existing acrylic or polyurethane coatings and most painted surfaces. #972 SEBS Elastomeric Coating may be applied to APP, SBS, and BUR roofing.

**PREPARATION:** All surfaces to be coated must be clean, dry, and free from dirt, oil, grease, and rust. Newly poured concrete must cure a minimum of 30 days prior to application of #972. Metal and wood must be primed with Elastomeric Primer at the rate of 1/2 to 3/4 gallon per 100 square feet.

**APPLICATION:** Recommended application for #972 SEBS Elastomeric Coating is by brush, spray, or roller. Apply two gallons per 100 square feet in two applications (one gallon of base and one gallon of top coating). Allow base coat (Stain Blocker) to cure thoroughly prior to application of the finish coat. Curing will take 12 to 24 hours dependent upon ambient temperatures and humidity.

**PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48–72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER** or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry.

**THIS PRODUCT HAS EXCELLENT PONDING WATER RESISTANCE. FOR BEST LONG-TERM PERFORMANCE, IT IS GOOD PRACTICE FOR ROOFS TO EXHIBIT POSITIVE DRAINAGE.**

**CLEANUP:** Clean tools with mineral spirits or paint thinner.

**CAUTION! COMBUSTIBLE!**

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

**MAXIMUM V.O.C = 550 G/L**  
**ELONGATION — 875%**  
**PERMEANCE — 1.3**  
**VISCOSITY @ 77°F, KU— 115 +/- 5**  
**DENSITY(WPG) — 9.5 +/- .4**  
**CURE TIME — AVERAGE: 12-24 HOURS**



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091