



## #990 ETERNALASTIC EPDM RINSEABLE WASH

TROPICAL ROOFING PRODUCTS' #990 ETERNALASTIC EPDM RINSEABLE WASH is a rinseable, low viscosity, spray- able liquid used as a pre-treatment of EPDM rubber roofing and Single-Ply membrane prior to power washing and application of Eternalastic coating. The unique chemistry is designed for use with Eternalastic and EternaSil coatings. Pre- treatment with #990 Eternalastic EPDM Primer significantly improves the adhesion of the topcoat to the EPDM rubber membrane.

**PREPARATION:** Surface to be repaired or coated must be clean, dry, and free of dust and dirt. #990 should be applied with a conventional compressive air sprayer/Hudson sprayer at a rate of 0.20 gallons per 100 square feet. Allow the #990 to dwell on the surface of the EPDM for 20-90 minutes, depending on the age of the EPDM substrate; the older and more aged the EPDM, the shorter the dwell time needs to be for adequate adhesion. The EPDM substrate must next be pressure washed with water at the rate of 2500 psi to remove the dwelling coating. While pressure washing, push the rinse water towards and drains, scuppers, or downspouts to ensure that the #990 is completely removed from the roof. Any residue of the #990 left on the EPDM will limit the adhesion capabilities of the top coat to the EPDM membrane. A second pass of pressure washing will help ensure that the #990 is properly rinsed from the EPDM substrate, again driving the rinse water towards drains, scuppers, and downspouts.

**COVERAGE:** Apply at a rate of approximately 1 gallon per 500 square feet (0.20 gal/Square).

**PRECAUTIONS:** DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE.

**DO NOT THIN. DO NOT HEAT CONTAINER** or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry.

**DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.**

**CLEANUP:** Clean tools with soap and water or Tropical #651 UltraClean Tool Cleaner.

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

**MAXIMUM V.O.C = 0 G/L**  
**DENSITY — 8.46 WPG**  
**APPEARANCE — CLEAR**  
**SOLUBLE IN WATER**  
**PH — Alkaline**  
**DWELL TIME — 20-90 minutes**



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAIDRIVE  
PORT ARTHUR, TX 77640  
866.727.0091