



## #101 ALL WEATHER PLASTIC CEMENT

**TROPICAL ROOFING PRODUCTS' #101 ALL WEATHER PLASTIC CEMENT** is a multi-purpose professional grade asphaltic-based plastic cement that adheres and spreads easily to all prepared surfaces including patching splits, seams and cracks in roof surfaces such as mineral surfaced cap sheet, smooth surface asphalt roofs, composition shingle, metal roofs and spudded gravel. Tropical Roofing Products #101 can also be used for repairing areas around chimneys, skylights, vent pipes, gravel guards, down spouts, splits in concrete, and expansion joints on roofs. Tropical Roofing Products #101 will not sag, slip or mud crack and remains highly resilient and durable throughout all seasons. Tropical Roofing Products #101 is a carefully mixed homogeneous blend of high-grade fibers, select asphalt, minerals, plasticizers and aromatic hydrocarbons. Meets ASTM D 4586 and ASTM D 3409. Miami-Dade NOA Compliant.

**PREPARATION:** Surface must be clean and free from rust or any other foreign matter that would interfere with a good bond. Remove rust with a wire brush. For best results in cold weather, store at room temperature for 24 hours prior to application.

**APPLICATION:** Use a trowel, putty knife or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2"-4" beyond the problem area feathering the edges. Embed glass fabric to reinforce cement, then cover with additional cement, if problem area is over 1/4" wide or 2" long.

**COVERAGE:** APPLY AT A MINIMUM RATE OF 20 LINEAR FT PER GALLON WITH 4" WIDE 1/8" THICK APPLICATION. Apply with a trowel or knife.

**PRECAUTIONS:** DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure lid is tight and pail is secure when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

**CLEANUP:** Clean tools with mineral spirits or paint thinner.

### CAUTION! COMBUSTIBLE!

Contains petroleum distillate. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION! Avoid contact with skin and breathing of vapor. CLOSE AIR INTAKES on roof until solvents dissipate. KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Contains volatile solvents that might contaminate potable water.

MAXIMUM V.O.C = 250 G/L  
CONSISTENCY — THICK MASTIC  
WEIGHT — 8.8 LBS. PER GAL  
FLASH POINT (T.C.C.) — 105°F+  
SERVICE TEMPERATURE (RANGE) — 40°F–90°F  
RESISTANCE TO ACIDS, ALKYS — EXCELLENT

ASTM D 4586  
ASTM D 3409



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091