



QUICK-DRY ASPHALT PRIMER

ASTM D 41, FES SPEC SS-A-701



- Premium quality Quick-Dry Asphalt Primer
- Solvent-based penetrating sealer
- Unsurpassed resiliency and durability
- Exceeds all the requirements of ASTM D 41 and FED SPEC SS-A-701
- Miami-Dade County Approved



FLORIDA
1904 SW 31ST AVE
HALLANDALE, FL 33009
800.432.2855


CALIFORNIA
14435 MACAW STREET
LA MIRADA, CA 90638
877.827.2622

TEXAS
1225 BRAI DRIVE
PORT ARTHUR, TX 77640
866.727.0091




QUICK-DRY ASPHALT PRIMER

ASTM D 41, FES SPEC SS-A-701



TROPICAL ROOFING PRODUCTS #410 Quick Dry Asphalt Primer is a fast-drying solvent-based bond coat and penetrating sealer for priming most surfaces prior to application of cold applied or hot mopped asphalt coatings, roof cements, adhesives, asphalt damp proofing and waterproofing. Not recommended as a stand-alone roof coating. Meets ASTM D 41, FED SPEC SS-A-701.



MAXIMUM V.O.C.....	350 G/L
CONSISTENCY	MEDIUM- BODIED LIQUID
WPG.....	7.7 LBS.
FLASH POINT (T.C.C.)	105°F

APPLICATION TOOLS

Heavy Duty Sprayer, Heavy Duty Paint Roller, or Squeegee



Availability in Gallons

TANKER	DRUM	PAIL
	 55	 5

CAUTION! COMBUSTIBLE: Contains petroleum distillate. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION! Avoid contact with skin and breathing of vapor. CLOSE AIR INTAKES on roof until solvents dissipate. KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Contains volatile solvents that might contaminate potable water