



## #501 PREMIUM ALL WEATHER ROOF MASTIC

**TROPICAL ROOFING PRODUCTS' #501 PREMIUM ALL WEATHER ROOF MASTIC** is a professional grade mastic with buttery smooth consistency fortified with **Power Gel Technology** that adheres to most surfaces wet or dry. 501 All Weather Premium Roof Mastic is formulated for use with built-up systems, SBS modified bitumen membranes, base tile roofs sheets, ply sheets, shingles and other approved surfaces. This product is easily spread and used to repair leaks, cracked spots, and holes in shingles. Easily applied around all flashings including skylights, gutters, and in all crevices. Readily adheres to all prepared surfaces by using trowel or glove. This Homogeneous and tough blend will not slip or mud crack. It will remain highly resilient and durable through all seasons in all weather. Recommended to be applied with cotton or yellow fabrics in a 3-course manner.

**PREPARATION:** Surface must be clean and free from rust or any other foreign matter that would interfere with a good bond. For best results in cold weather, store at room temperature for 24 hours prior to application.

**APPLICATION:** Use a trowel, putty knife, or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2"-4" beyond the problem area feathering the edges. Embed fabric to reinforce cement, then cover with additional cement, if problem area is over 1/4" wide or 2" long.

**COVERAGE:** APPLY AT A MINIMUM RATE OF 40 LINEAR FT PER GALLON WITH 4" WIDE 1/8" THICK APPLICATION .  
**NOTE:** DO NOT use on APP, TPO, EPDM, PVC

**PRECAUTIONS:** DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

Contains petroleum distillate. Keep away from heat and flame. USE ONLY WITH ADEQUATE VENTILATION! Avoid contact with skin and breathing of vapor. CLOSE AIR INTAKES on roof until solvents dissipate. KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Contains volatile solvents that might contaminate potable water

MAXIMUM V.O.C = 250 G/L  
CONSISTENCY — THICK MASTIC, APPLY BY TROWEL  
WEIGHT — 8.7 LBS. PER GAL +/-2  
FLASH POINT (T.C.C.) — 105°F+  
SERVICE TEMPERATURE (RANGE) — 40°F-90°F  
RESISTANCE TO ACIDS, ALKYDS — EXCELLENT

ASTM D 4586  
ASTM D 3409



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091