



## #935 HIGH TENSILE MICRO-FIBERS

Thickening and Strengthening Agent for Silicone

**TROPICAL ROOFING PRODUCTS' #935** is a micro-fine manufactured high tensile polyethylene fiber used as a general thickener to increase tensile strength and reduce sag for Tropical Roofing Products silicone coatings. #935 Micro-Fiber allows excellent melding to silicone without slipping. Adding Micro Fiber also creates a smooth easy-to-apply material to greatly increase viscosity and filling ability of the coating at an economical price. Allows a higher viscosity and excellent vertical hold for a variety of applications. Retains elastic properties, increases tensile strength and improves bridging strength. Easily mixed in with hand tools at a ratio of 20% - 50% by volume.

**PREPARATION:** Surface to receive coating must be clean, smooth, dry, and paintable. Any debris, gravel, dust, and silt must be removed prior to application.

**WEATHER RESTRICTIONS:** It is very important that this product is not used when weather conditions are below 50°F, or when there is a chance that temperatures could fall below 32°F within a 24 hour period after application. We also do not recommend application of this product if rain or dew is likely to occur before curing of product.

**MIXING PROCEDURES:** Easily mixed in with hand tools at a ratio of 20%-50%. • Addition of Micro Fibers to silicone will shorten pot life. Do not add more than one hour in advance. Do not mix more than you will use during one working period.

**CLEAN UP:** Sweep or vacuum dry fibers.

**WARNING:** This product may be mixed with coating which contain flammable solvents and is designed for professional installation. Caution should be exercised to prevent mishap due to improper handling. The use of an appropriate MESA/ NIOSH approved respirator during application is important. We also recommend the use of fabric coveralls and neoprene or other resistant gloves. Installers should use caution during spray processes to avoid falls caused by slipping on wet primer. Installers should read and understand all technical and informational literature on this product, including the Safety Data Sheet, prior to using this product.

**MELTING POINT: 248°F - 271°F (120°C -**

**133°) FLASH POINT: 665°F (352°C)**

**SPECIFIC GRAVITY: .0915 - .0965**

**PH: 1.5 -7.0**

**SHELF LIFE: INDEFINITE**


**APPEARANCE: FLUFFY FIBER**

**COLOR: WHITE**

**STORAGE: KEEP MATERIAL DRY**

**CLEANUP: SWEEP OR VACUUM**

**HMIS®: Health 0, Flammability 1, Reactivity 0, Protection X ( 0=Minimal1=Slight 2=Moderate3=Serious4=Severe)**



FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORTARTHUR, TX 77640  
866.727.0091