



#950 ETERNAMASTIC ELASTOMERIC ROOF MASTIC

TROPICAL ROOFING PRODUCTS' #950 ETERNAMASTIC ELASTOMERIC ROOF MASTIC is a tough, tenacious and durable white elastomeric flashing compound. Provides superior hiding power, is highly reflective, and is easy to apply. Ideal for laps, cracks, seams, directional wall changes, screw heads, and roof penetrations. Miami-Dade NOA.

PRODUCT APPLICATION INCLUDES: Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

PRE-TREATMENT: Treat all surfaces with the appropriate Eternalastic primer.

COVERAGE: Apply at a minimum rate of 25–30 linear feet per gallon with 4" to 6" wide 1/8" thick application.

CURE: Cures by ultra violet rays; allow for sufficient daylight. Cure time affected by environmental conditions.

PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48–72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. **DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.**

CLEANUP: Clean tools with mineral spirits, paint thinner, or soap and water.

KEEP OUT OF REACH OF CHILDREN. Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!**

Low VOC, SCAQMD Compliant
Volume Solids — 42%
Weight Solids — 55%
Viscosity — Brush Grade
Tensile Strength — 200+ psi
Elongation — 200+%



FLORIDA
1904 SW 31ST AVE
HALLANDALE, FL 33009
800.432.2855

CALIFORNIA
14435 MACAW STREET
LA MIRADA, CA 90638
877.827.2622

TEXAS
1225 BRAI DRIVE
PORT ARTHUR, TX 77640
866.727.0091