



#970 ETERNALASTIC ACRYLIC CONCRETE PRIMER

TROPICAL ROOFING PRODUCTS' #970 ETERNALASTIC CONCRETE PRIMER is a water based, easily applied product that was developed to help ensure superior finished coating adhesion. #970 Eternalastic Concrete Primer is to be used when applying any Eternalastic product to any structural concrete surface. This primer will absorb into the concrete thus preparing the surface for maximum performance and adhesion. #911 Eternalastic Coating should not be applied to unprimed concrete.

PRODUCT APPLICATION INCLUDES: Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

PRE-TREATMENT: Treat all surfaces with the appropriate Eternalastic primer.

DRYING TIME: 2-4 hours dependent on temperature and humidity.

COVERAGE: 100 – 200 SF per gallon, dependent on surface texture and absorbency.

PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48–72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry.

DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

CLEANUP: Clean tools with mineral spirits or paint thinner.

CAUTION! COMBUSTIBLE!

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

MAXIMUM V.O.C = 99 G/L
WEIGHT SOLIDS — 25%
VISCOSITY — 80-90 KU
LIQUID APPEARANCE — WHITE
DRY APPEARANCE — CLEAR
DRYING TIME — AVERAGE: 2-4 HOURS



