



## **#9900 ETERNASIL TPO PRIMER**

### ***For Enhanced Adhesion of Silicone Coatings over TPO***

**TROPICAL ROOFING PRODUCTS' #9900 Eterna-Sil TPO Primer** is intended to be used over aged/existing TPO membranes. #9900 is a green, very thin, watery-like fluid that should be applied only by brush. The coverage rate for this product is intended to be a minimum of 800 ft<sup>2</sup> per gallon or 8 squares per gallon. Total wet film application is only 2 wet mils maximum. Spread the product across the substrate until a greenish sheen is no longer visible. The product should dry clear with an undetected or very subtle green tint if installed correctly. Achieving a thinner coverage rate for this product is better for adhesion. This product dries very quickly as it is mostly solvent.

**PREPARATION:** TPO must be cleaned and prepared properly prior to applying the 9900 Eterna-Sil TPO Primer. Surface must be clean, dry, and free of moisture both on and beneath the surface. Pressure wash roof thoroughly to remove as much dust, dirt, and debris as possible. After careful inspection of entire roof, repair all holes, cracks, tears, or breaks in TPO membrane.

**APPLICATION:** Spread #9900 across the substrate until the greenish sheen is no longer visible. The product should dry clear with a very subtle or undetected hue of green if installed correctly. The application of silicone over this primer can be conducted after 2 hours of drying.

**COVERAGE:** Apply at a maximum rate of 1 gallon per 800 sq. feet per coat dependent upon roof porosity.

**PRECAUTIONS: DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48–72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER** or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry.

**CLEANUP:** Clean tools with mineral spirits or paint thinner.

### **CAUTION!**

KEEP OUT OF REACH OF CHILDREN. Close container after each use. **DO NOT TAKE INTERNALLY!** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!**

FLORIDA  
1904 SW 31ST AVE  
HALLANDALE, FL 33009  
800.432.2855

CALIFORNIA  
14435 MACAW STREET  
LA MIRADA, CA 90638  
877.827.2622

TEXAS  
1225 BRAI DRIVE  
PORT ARTHUR, TX 77640  
866.727.0091

PACIFIC NORTHWEST  
14325 NE AIRPORT WAY SUITE 107  
PORTLAND, OR 97230  
844.854.9323