

Application Rates and Spray Tip Sizes

PRODUCT	PRODUCT NAME	COATS	COVERAGE*	PSI**	GAL/MIN	TIP SIZE	FAN***
106	Non-Fibered Aluminum Roof Coating	1	.05-1 Gal.	3000	1.5 Gal.	.033-.067	6"
120	Fibered Aluminum Roof Coating	1	1-1.5 Gal.	3000	1.5 Gal.	.051-.067	6"
126	Non-Fibered Aluminum Roof Coating	1	.05-1 Gal.	3000	1.5 Gal.	.033-.067	6"
360	Non-Fibered Asphalt Emulsion	2	3-4 Gal. Coat	3000	2-8 Gal.	.0861<	6-12"
363	Fibered Asphalt Emulsion	2	3-4 Gal. Coat	1500	2-8 Gal.	.0861<	6-12"
365	Modified Asphalt Emulsion	2	2-3 Gal. Coat	1500	2-8 Gal.	.0861<	6-12"
367	Neoprene Modified Asphalt Emulsion	2	2-3 Gal. Coat	1500	2-8 Gal.	.0861<	6-12"
642	Crystal Clear Tile Sealer	2	1 Gal.	1000	.5 Gal.	.0051<	8"
901	White Elastomeric Roof Coating	2	1-2 Gal. Coat	2000 Min.	4 Gal.	.0631<	12-18"
911	Eternalastic White Elastomeric Roof Coating	1	1-2 Gal. Coat	2000 Min.	2 Gal.	.0631<	12-18"
914	Eterna-Sil Silicone	1	1.5-2 Gal. Coat	3300 Min.	2.2 Gal.	.027-.031	10-12"
921	Reflex White Elastomeric Roof Coating	1	1-2 Gal. Coat	2000 Min.	3 Gal.	.0631<	12-18"
960	Eternalastic Metal Primer	1	1 Gal.	1000	1 Gal.	.025-.067	6-12"
970	Eternalastic Concrete Primer	1	0.5 Gal.	1000	1 Gal.	.025-.067	6-12"
980	Eternalastic Acrylic Asphalt Primer	1	1 Gal.	1000	1 Gal.	.025-.067	6-12"
985	Eternalastic Water Based Primer	1	.02 Gal.	1000	.20 Per Sq.	.0861<	6-12"
990	Eternalastic EDPM Rinseable Primer	1	.02 Gal.	Hudson Sprayer	.20 Per Sq.	Hudson Sprayer	Hudson Sprayer
4003	Fibered Resaturant and Sealer	1	3 Gal.	1000	3 Gal.	0.051	8"

*COVERAGE IS BASED ON COAT AND SATURATION PER 100 SQ. FT.

AMBIENT TEMPERATURE WILL EFFECT SPRAYABILITY. SIZE AND LENGTH OF HOSE WITH ELEVATION WILL EFFECT SPRAYER OUTPUT. *FAN WIDTH MAY VARY