



508 WET SURFACE MODIFIED MASTIC

APPLICATION METHODS



Application rates will vary by surface, porosity, and job conditions.

AVAILABLE SIZES



#508 Wet Surface Modified Mastic is a professional grade rubber modified soft and pliable mastic specially formulated for superior adhesion under severe cold and or wet surface conditions, even in driving rain or under water. **#508's** unique formulation is designed for repairing leaks, cracked spots, holes in shingles, concrete, and steel or metal roofs. Fortified with Power Gel Technology so it will remain highly resilient and durable through all seasons. Meets ASTM D 4586 and ASTM D 3409. Miami-Dade NOA Compliant.



MIAMI-DADE COUNTY
APPROVED





PRODUCT DESCRIPTION

Tropical Roofing Products' #508 Wet Surface Modified Mastic is a dependable rubber modified soft and pliable mastic specially formulated for superior adhesion under severe cold and or wet surface conditions, even in driving rain or under water. **#508's** unique formulation is designed for repairing leaks, cracked spots, holes in shingles, concrete, and steel or metal roofs. Fortified with Power Gel Technology so it will remain highly resilient and durable through all seasons. Meets ASTM D 4586 and ASTM D 3409.

PHYSICAL PROPERTIES

V.O.C	<250 g/L
Consistency	Thick Soft Mastic
Weight	8.7 lbs per gallon

Flash Point (TCC)	105°F +
Service Temp	45°F +
Resistance to Acids/Alkyds	Excellent

PREPARATION

Surface must be free from rust or any other foreign matter that would interfere with a good bond. Remove rust with a wire brush. For best results in cold weather, store at room temperature for 24 hours prior to application.

APPLICATION

Use a trowel, putty knife or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2"-4" beyond the problem area feathering the edges. If problem area is over 1/4" wide or 2" long embed glass fabric to reinforce cement then cover with additional cement.

COVERAGE

Approximate coverage is 12 square feet per gallon. Apply at a minimum rate of 40 linear ft. per gallon with 4" wide 1/8" thick application.

PRECAUTIONS

DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

CLEANUP

Clean tools with mineral spirits or paint thinner.



KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.