




# 642 "CRYSTAL" CLEAR ROOF TILE SEALER

## APPLICATION METHODS



Application rate at a minimum of 1.0 gallons per 100 square feet done in multiple coats. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

## AVAILABLE SIZES



## AVAILABLE STANDARD COLORS



Clear



**#642 "Crystal" Clear Tile Sealer** is a 100% acrylic, transparent, professional grade tile sealer that will keep your roof looking clean and new. **#642 "Crystal" Clear Tile Sealer** will repel water, weatherproof, protect and extend the life of your tile roof.





### PRODUCT DESCRIPTION

#642 "Crystal" Clear Tile Sealer is a 100% acrylic, transparent, professional grade tile sealer that will keep your roof looking clean and new. #642 "Crystal" Clear Tile Sealer will repel water, weatherproof, protect and extend the life of your tile roof.

### FEATURES + BENEFITS

- Long Lasting Protection
- Resistant to UV Rays
- Extends the Life of your Tile Roof
- Built in Fungicides and Algaecides
- Provides Alkali Resistance
- Natural, Transparent Finish when Dry

### PHYSICAL PROPERTIES

V.O.C	50 g/L
Appearance (Wet)	Milky White
WPG Nominal	8.7

Flash Point	Not Applicable
Dry Film	Clear
Drying Time Average	2-4 hours (to touch)

### PREPARATION

Surface must be clean and dry, free of moisture on the surface. Pressure wash roof thoroughly to remove as much dust, dirt and debris as possible. Let surface dry completely before application.

### APPLICATION

#642 "Crystal" Clear Tile Sealer can be applied to a dry surface. Shake or stir #642 "Crystal" Clear Tile Sealer thoroughly before application to achieve a uniform consistency. Apply by sprayer, brush or roller. Use product when outside temperatures is 50°F or higher. DO NOT HEAT CONTAINER. DO NOT THIN.

### COVERAGE

A application rate of 200 - 300 sq. ft. per gallon is required. The application rate will vary due to surface porosity. Allow the first coat to dry a minimum of 3 hours. For best results a second coat can be applied at the rate of 350 to 400 sq. ft. per gallon.

### PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50°F or above 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail

to tumble as this may loosen the lid and allow leakage or spillage to occur. DO NOT ALLOW PRODUCT TO FREEZE. Do not heat container or store at temperatures greater than 120°F. This coating is not recommended for areas with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

### CLEANUP

If coating has dried clean tools with mineral spirits or paint thinner. If coating is still wet, clean up with warm soapy water.

### PACKAGE SIZES

Available in 1-gallon pails, 5-gallon pails and 55-gallon drums.

### SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

CONTAINER SIZE	CLASS
5 Gal.	55
55 Gal.	5

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!



To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.