



651 ULTRACLEAN ASPHALT AND TAR REMOVER

APPLICATION METHODS



Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES

32 Ounce Spray Bottle
[12 bottles/carton]



#651 UltraClean Asphalt and Tar Remover is a heavy-duty, biodegradable, non-toxic petroleum-free cleaner/degreaser with all natural ingredients. **#651 UltraClean Asphalt and Tar Remover's** natural citrus spray cleaner is non-caustic, non-acid, and non-corrosive. UltraClean Asphalt and Tar Remover effectively dissolves and removes the toughest grease, tar, asphalt products, adhesives, roof and foundation coatings, and other petroleum based products. **#651 UltraClean Asphalt and Tar Remover** can be safely used to clean tools, equipment, after spills, splatter or over-spray on aluminum, stainless steel, chrome, concrete, and most plastics and painted surfaces.





651 ULTRACLEAN ASPHALT AND TAR REMOVER

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

#651 UltraClean Asphalt and Tar Remover is a heavy-duty, biodegradable, non-toxic petroleum-free cleaner/degreaser with all natural ingredients. **#651 UltraClean Asphalt and Tar Remover's** natural citrus spray cleaner is non-caustic, non-acid, and non-corrosive. UltraClean Asphalt and Tar Remover effectively dissolves and removes the toughest grease, tar, asphalt products, adhesives, roof and foundation coatings, and other petroleum based products. **#651 UltraClean Asphalt and Tar Remover** can be safely used to clean tools, equipment, after spills, splatter or over-spray on aluminum, stainless steel, chrome, concrete, and most plastics and painted surfaces.

FEATURES + BENEFITS

- Heavy-duty, Biodegradable, Non-toxic Petroleum-free Cleaner/Degreaser
- Made with All-natural Ingredients
- Non-caustic, Non-acid and Non-corrosive
- Dissolves and Removes the Toughest Grease, Tar, Asphalt Products, Adhesives, Roof and Foundation Coatings and Other Petroleum-based Products
- Can Be Safely Used to Clean Tools, Equipment, After Spills, Splatter or Over-spray on Aluminum, Stainless Steel, Chrome, Concrete and Most Plastics and Painted Surfaces

APPLICATION

Do not thin or dilute.

TOOL CLEANER: Spray **#651 UltraClean Asphalt and Tar Remover** full strength to a dry surface and allow to penetrate for a few minutes. Hose off completely with strong stream of water.

HARD SURFACES: Let **#651 UltraClean Asphalt and Tar Remover** remain on the surface until spot or stain appears loosened, then rinse with water to remove residue.

FABRICS: Wet fabric with **#651 UltraClean Asphalt and Tar Remover**, rub into stain and wash article in washing machine.

CARPETING:- Apply **#651 UltraClean Asphalt and Tar Remover** sparingly and blot stain lightly. Blot again with clean cloth and repeat as necessary. When finished, rinse with water.

NOTE: **#651 UltraClean Asphalt and Tar Remover** is a solvent. Always test this product on an inconspicuous area before use.

SPECIFICATIONS

85-90% Limonene Solvent.

PRECAUTIONS

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of the reach of children. Keep container covered when not in use. Do not thin or dilute. Dispose of in an environmentally friendly manner.

VOC COMPLIANCE

#651 UltraClean Asphalt and Tar Remover is compliant with all national, state and district VOC regulations.



KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.