



701 ALL WEATHER FLASHING CEMENT

APPLICATION METHODS



Application rates will vary by surface, porosity, and job conditions.

AVAILABLE SIZES



#701 All Weather Flashing Cement is a professional grade asphaltic base flashing cement that adheres to all surfaces wet or dry. Readily adheres to all prepared surfaces, and will not sag, slip, or mud-crack. A multipurpose flashing cement for repairing leaks, cracked spots, holes in shingles, concrete, and steel or metal roofs. Can be used on all flashings around skylights, gutters, and in all crevices. Meets and exceeds all the requirements of ASTM D 4586 and D 3409.



MIAMI-DADE COUNTY
APPROVED





PRODUCT DESCRIPTION

Tropical Roofing Products' #701 All Weather Flashing Cement is a contractor grade asphaltic base flashing cement that adheres to all surfaces wet or dry. Readily adheres to all prepared surfaces, and will not sag, slip, or mud crack. A multipurpose flashing cement for repairing leaks, cracked spots, holes in shingles, concrete, and steel or metal roofs. Can be used on all flashings around skylights, gutters, and in all crevices. Meets ASTM D 4586 and ASTM D 3409. Miami-Dade NOA Compliant.

PHYSICAL PROPERTIES

V.O.C	<250 g/L
Consistency	Thick Soft Mastic
Weight	8.7 lbs per gallon

Flash Point (TCC)	105°F +
Service Temp	45°F +
Resistance to Acids/Alkyds	Excellent

PREPARATION

Surface must be clean and free from rust or any other foreign matter that would interfere with a good bond. For best results in cold weather, store at room temperature for 24 hours prior to application.

APPLICATION

Use a trowel, putty knife or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2"-4" beyond the problem area feathering the edges. Embed fabric to reinforce cement, then cover with additional cement, if problem area is over 1/4" wide or 2" long.

COVERAGE

Apply at a minimum rate of 40 linear ft. per gallon with 4" wide 1/8" thick application.

PRECAUTIONS

DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

CLEANUP

Clean tools with mineral spirits or paint thinner.



KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.