



805 COMMERCIAL GRADE ROOF CEMENT

APPLICATION METHODS



Application rate of approximately 40 linear feet per gallon with 4" wide 1/8" thick application. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES



#805 Commercial Grade Roof Cement is a professional grade asphaltic base plastic cement. **#805** is ready to use as it comes out of the can and can be applied with a trowel or knife. **#805** is a carefully mixed homogeneous blend of high-grade fibers, select asphalt, minerals, plasticizers, and aromatic hydrocarbons. **#805** readily adheres to all prepared surfaces and will not sag, slip, or mudcrack, and will remain highly resilient and durable through all seasons. **#805** is a multipurpose plastic cement for repairing leaks, cracked spots, holes in shingles, concrete and steel or metal roofs. **#805** can be used on all flashings around skylights, gutters, and in all crevices.





PRODUCT DESCRIPTION

#805 Commercial Grade Roof Cement is a professional grade asphaltic base plastic cement. **#805** is ready to use as it comes out of the can and can be applied with a trowel or knife. **#805** is a carefully mixed homogeneous blend of high-grade fibers, select asphalt, minerals, plasticizers, and aromatic hydrocarbons. **#805** readily adheres to all prepared surfaces and will not sag, slip, or mudcrack, and will remain highly resilient and durable through all seasons. **#805** is a multipurpose plastic cement for repairing leaks, cracked spots, holes in shingles, concrete and steel or metal roofs. **#805** can be used on all flashings around skylights, gutters, and in all crevices.

FEATURES + BENEFITS

- Multi-Purpose, Commercial-Grade Roof Cement
- Formulated to Repair Leaks, Cracked Spots, Holes in Shingles, Concrete, and Steel or Metal Roofs.
- Versatile Tough Blend That Will Not Slip or Mud Crack
- Recommended to Apply With Cotton or Poly Fabrics in a 3-Course Manner

PHYSICAL PROPERTIES

Maximum V.O.C.	250 g/L
Consistency	Thick soft mastic
WPG (Nominal)	8.7 lbs. per gal

PREPARATION

Surface must be clean and free from rust or any other foreign matter that would interfere with a good bond. Remove rust with a wire brush. For best results in cold weather, store at room temperature for 24 hours prior to application

APPLICATION

Use a trowel, putty knife or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2" - 4" beyond the problem area feathering the edges. Embed glass fabric to reinforce cement, and then cover with additional cement, if problem area is over 1/4" wide or 2" long.

COVERAGE

Apply at a minimum rate of 40 linear feet per gallon with 4" wide 1/8" thick application.

Flash Point (TCC)	105° F +
Service Temp	40°-90° F

CLEANUP

Clean tools with mineral spirits or paint thinner.

PRECAUTIONS

DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure lid is tight and pail is secure when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

CONTAINER SIZE	CLASS
1, 5 Gal.	5



KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.