



941 SAFETY WALKWAY COATING

APPLICATION METHODS



Application rate of 2.0 gallons per 100 square feet per coat dependent upon roof porosity. Additional reinforcing layers of polyester and coating may be applied to increase durability and longevity of the safety walkway system. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES



AVAILABLE STANDARD COLORS



Safety Yellow



#941 Safety Walkway Coating is intended to be applied over newly applied or existing acrylic roof restoration systems. The anti-skid material present in the coating allows for individuals to access mechanical, HVAC, and auxiliary components that exist across the roofing terrain in a slip-free and safe way. The increased grip and traction provided by the **#941 Safety Walkway Coating** makes traversing the roof safer than a traditional fluid applied system.





PRODUCT DESCRIPTION

#941 Safety Walkway Coating is intended to be applied over newly applied or existing acrylic roof restoration systems. The anti-skid material present in the coating allows for individuals to access mechanical, HVAC, and auxiliary components that exist across the roofing terrain in a slip-free and safe way. The increased grip and traction provided by the **#941 Safety Walkway Coating** makes traversing the roof safer than a traditional fluid applied system.

FEATURES + BENEFITS

- Fast Dry
- Low VOC
- Single Component Material
- Excellent Adhesion
- Water-based
- Easy to Apply by Roller
- Increased Grip and Traction

PRODUCT LIMITATIONS

#941 should not be applied to wet, dusty, oily, mildewed, heavily chalked, blistered or otherwise structurally unsound surfaces. Do not apply **#941** over silicone, TPO, EPDM or PVC systems without an appropriate primer. This product is not intended to replace any OSHA required slip, fall, and harness equipment for roof safety.

PREPARATION

All surfaces to be coated must be clean, dry, and paintable. It may be necessary to power wash to enhance adhesion. See application specification for more details.



PHYSICAL PROPERTIES

| | |
|------------------|-------------|
| V.O.C. | <50 g/L |
| Weight by Gallon | 10 lbs./gal |

MIXING PROCEDURES

#941 should be lightly hand-mixed to uniformity prior to application.

APPLICATION EQUIPMENT

#941 can be applied by short nap or smooth roller.

APPLICATION

For ideal drying conditions, apply on warm, sunny days, preferably in the morning hours to provide maximum dry time. **#941** can be applied to a dry or slightly damp, but not wet, surface. Water must be swept out of all puddles prior to application of **#941**. Stir thoroughly before application to achieve a uniform consistency. Apply with a short nap, smooth, or heavy-duty paint roller. Under normal conditions, allow **#941** to dry in 24 hours for light foot traffic and at least 72 hours for heavy foot traffic. Relative humidity and temperature will directly affect drying time. Avoid over application. Ideal for where anti-slip surfaces are desired.

For enhanced durability and longevity, apply a base layer of **#941** coating at a rate of 2.0 gallons per square followed a layer of reinforcing polyester fabric applied over the wet base layer of coating followed by a second layer of coating at 2.0 gallons per square over the polyester. Apply each layer of coating in a cross-hatch manner.

| | |
|------------------|-----|
| Solids by Volume | 52% |
|------------------|-----|

COVERAGE

Apply at a rate of 2.0 gallons per 100 sq. feet per coat dependent upon roof porosity. Additional reinforcing layers of polyester and coating may be applied to increase durability and longevity of the **#941 Safety Walkway Coating**.

PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

CLEANUP

Clean wet coating from hands and tools with soap and water. Dried coating on tools can be cleaned with mineral spirits or paint thinner.

PACKAGE SIZES

Available in 5-gallon pails.

SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

| CONTAINER SIZE | CLASS |
|----------------|-------|
| 5 Gal. | 55 |

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.