



950 ETERNAMASTIC ELASTOMERIC ROOF MASTIC

APPLICATION METHODS



Application rate at a minimum of 25-35 lineal feet per gallon with a 4-6" wide application at 1/8" thick. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES



AVAILABLE STANDARD COLORS



White



#950 Eternamastic Elastomeric Roof Mastic is a tough, tenacious and durable white compound with high grade components. **#950** was developed and is designed to be a superior reflective material for new roofing, re-roofing, and roof maintenance markets. **#950's** high pigment level provides superior hiding power, is highly reflective, easy to apply, and has superior hiding power. It has multiple application uses including laps, cracks, seams, directional wall changes, screw heads, and roof intrusions.





PRODUCT DESCRIPTION

#950 Eternamastic Elastomeric Roof Mastic is a tough, tenacious and durable white compound with high grade components. **#950** was developed and is designed to be a superior reflective material for new roofing, re-roofing, and roof maintenance markets. **#950's** high pigment level provides superior hiding power, is highly reflective, easy to apply, and has superior hiding power. It has multiple application uses including laps, cracks, seams, directional wall changes, screw heads, and roof intrusions.

FEATURES + BENEFITS

- Miami-Dade County Approved
- Helps Protect Against Mold and Mildew
- Ideal for Patching Flashings and Penetrations
- Can Be Used with Polyester Fabric
- Superior Hiding Power
- Ready to Use

PHYSICAL PROPERTIES

V.O.C	<15 g/L
Solids by Volume	42%
Solids by Weight	55%

PRODUCT APPLICATION

Laps, cracks, seams, directional wall changes, screw heads, roof intrusions.

PRE-TREATMENT

Treat all surfaces with the appropriate Eternalastic primer.

COVERAGE

Application rate at a minimum of 25-35 lineal feet per gallon with a 4-6" wide application at 1/8" thick.

CURE

Cures by ultra violet rays; allow for sufficient daylight. Cure time affected by environmental conditions.

PRECAUTIONS

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. This coating is not recommended for areas

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

Viscosity	Brush Grade
Tensile Strength	200+ psi
Elongation	200+%

with inadequate drainage (ponding water), over gravel, over walking decks, or old roofs that are too brittle and dry. DO NOT APPLY TO FLAT SURFACES WITH POOR DRAINAGE OR WHERE PONDING WATER WILL EXIST.

CLEANUP

Clean tools with mineral spirits, paint thinner, or soap and water.

SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

CONTAINER SIZE	CLASS
5 Gal.	55

