



997 MULTIPURPOSE PRIMER

APPLICATION METHODS



Application rate at a minimum of 1.0 gallons per 100 square feet. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

AVAILABLE SIZES



AVAILABLE STANDARD COLORS



Dark Green



#997 Multipurpose Primer is a highly engineered, single-component, water-based primer designed for application over TPO, Concrete, Galvalume, Galvanized Steel, Aluminum, and other common roofing substrates - including difficult to adhere to membranes or surfaces. **#997** is designed to improve adhesion of the topcoat to the substrate and imparts water-resistant qualities before the topcoat of silicone or acrylic coating are applied.





#997 MULTIPURPOSE PRIMER

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

#997 Multipurpose Primer is a highly engineered, single-component, water-based primer designed for application over TPO, Concrete, Galvalume, Galvanized Steel, Aluminum, and other common roofing substrates - including difficult to adhere to membranes or surfaces. **#997** imparts corrosion resistance to metal substrates laden with surface rust and is designed to improve adhesion of the topcoat to the substrate, providing water-resistant qualities before the topcoat is applied.

FEATURES + BENEFITS

- Adhesion Promoting
- Single Component Universal Primer for Acrylic and Silicone
- Rust Inhibiting Formula over Metal
- Fast Dry
- Low VOC
- Easy to Spray, Roll or Brush On

PRODUCT LIMITATIONS

#997 should not be applied to wet, dusty, oily, mildewed, heavily chalked, blistered or otherwise structurally unsound surfaces. Do not apply **#997** over silicone. Once cured, the **#997** will have a slightly tacky finish to the touch. It is advisable to wear some form of boot/shoe cover when walking on the finished coating while applying the topcoat.

PHYSICAL PROPERTIES

Color	Dark Green, Translucent
V.O.C	<50 g/L

PREPARATION

All surfaces to be coated must be clean, dry, and paintable. It may be necessary to power wash enhance adhesion. See application specification for more details.

APPLICATION

For ideal drying conditions, apply on warm, sunny days, preferably in the morning hours to provide maximum dry time. **#997** can be applied to a dry surface. Water must be swept out of all puddles prior to application of **#997**. Stir thoroughly before application to achieve a uniform consistency. Apply with a brush, heavy-duty paint roller, or heavy-duty spray equipment. Under normal conditions, **#997** will dry in 2 - 4 hours. Relative humidity and temperature will directly affect drying time. Avoid over application.

APPLICATION EQUIPMENT

#997 can be applied by brush, roller or spray.

COVERAGE

Apply at a rate of 1.0 gallon per 100 sq. feet per coat dependent upon roof porosity.

Density	8.6 lbs./gal
Solids by Volume	28%

PRECAUTIONS!

DO NOT APPLY IF TEMPERATURE IS BELOW 50° F OR ABOVE 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS. DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight, and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

CLEANUP

Clean wet coating from hands and tools with soap and water. Dried coating on tools can be cleaned with mineral spirits or paint thinner.

PACKAGE SIZES

Available in 5-gallon pails and 55-gallon drums.

SHIPPING INFORMATION

D.O.T. Classification: Roof Coating, Not Regulated NFMC #170080

CONTAINER SIZE	CLASS
5 Gal.	55
55 Gal.	5

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY!
If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!



To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.